


JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF26318-20B	LCD HIGH OUTPUT WHITE 5300°k RGB	1636 @ 0°C	676	5	34,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION					
			DRAWN BY L. WENGSTROM		APP'VD BY DATE F.D. 2/28/02		SIZE A		FSCM NO. 55335		DRAWING NO. BF26318-20B	
RELEASED 2/28/02			APP'VD DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		RELEASED DATE 2/28/02		REVISION DATE	
REV. NO.	DESCRIPTION/ECO NUMBER		APP'VD DATE		MANUAL REVISIONS NOT PERMITTED		SCALE NONE		RELEASED DATE 2/28/02		REVISION DATE	
											REV. NO. 1 OF 1	