

3M TOUCH SYSTEMS Touch Screens and Accessories MicroTouch

Read Complaint This product is RoHS complaint.

3M Touch Systems offers a wide portfolio of touch technologies and touch products with a commitment to ease of integration, responsiveness, reliability and simplicity of use. With its world-class support and service organization, 3M provides expert technical consulting service and support wherever any of our products are designed, integrated or delivered. It is this complete solution approach that ensures remarkable compatibility and exceptional service, backed by 3M.

MICROTOUCH™ CLEARTEK™ II TOUCH SENSORS

ClearTekTM II Touch Sensors offer a high-endurance capacitive touch solution that shrugs off on-screen contaminants such as chemicals, grease, dirt, and water without interrupting operation. Ideal for touch applications where exceptional performance, vibrant optics and environmental robustness is mission critical, 24-hours a day, 7 days a week.

Features:

- 91.5%(±1.5%) light transmission Resilient top coat
- 1024 x 1024 Resolution
- 3.18mm (±0.25mm) Glass thickness
- 6.4" to 32" diagonal Display size
 Operating Temperature -15°C to 70°C
 Note: All sensors have 8" Flex Tail

For quantities of 100 and up, call for quote.

MOUSER	3M Touch		5	F	Price Each	า
STOCK NO.	Systems Part No.	Fig.	Description	1	10	50
517-17-8091-205	17-8091-205	Α	6.71" with 5 Pin Locking Amp			
517-17-8021-205	17-8021-205	A	10.83" with 5 Pin Locking Amp			
517-17-8581-205	17-8581-205	A	12.31" with 5 Pin Locking Amp			
517-17-8031-205	17-8031-205	Α	15.68" with 5 Pin Locking Amp			
517-17-8031-225	17-8031-225	В	15.68" with USB controller			
517-17-8421-225	17-8421-225	В	17.54" with USB controller			
517-17-9241-225	17-9241-225	В	17.80" wide aspect with USB controller			
517-17-9251-225	17-9251-225	В	19.34" wide aspect with USB controller			
517-17-8511-205	17-8511-205	Α	19.75" with 5 Pin Locking Amp			
517-17-8511-225	17-8511-225	В	19.75" with USB controller			
517-17-8441-205	17-8441-205	A	20.65" with 5 Pin Locking Amp			
517-17-8441-225	17-8441-225	В	20.65" with USB controller			
517-17-9261-225	17-9261-225	В	20.65" wide aspect with USB controller			
517-17-9311-225	17-9311-225	В	22.37" wide aspect with USB controller			
517-17-8931-225	17-8931-225	В	26.28" wide aspect with USB controller	l		
517-17-8951-205	17-8951-205	A	31.80" wide aspect with 5 Pin Locking Amp			
517-17-8951-225	17-8951-225	В	31.80" wide aspect with USB controller			

MICROTOUCH™ TOUGHTOUCH II TOUCH SENSORS

ToughTouch II is 3M's most rugged capacitive touch product and its construction combines a MicroTouch ClearTek II capacitive touch sensor with a 4mm glass layer optically laminated to the back. With an overall thickness of 8mm, ToughTouch II is an ideal touch solution for unsupervised, vandal-prone environments where ruggedized a ruggedized, shatter-resistance touch solution is a must

- 86.5 % (± 1.5%) light transmission
- 7.57mm (± 0.58mm) Glass Thickness
 6.5" to 32" diagonal Display size
- Operating Temperature -15°C to 70°C 1024 x 1024 Resolution
- · Scratch resistant top coat

				For quanti	ties of 100	anu up, can	Tor quote
517-87-4061-211	87-4061-211	С	15.90" 8" Cable w/EXII-7710UC				
517-87-5961-211	87-5961-211	С	17.78" 8" Cable w/EXII-7710UC				
517-87-6001-211	87-6001-211	С	19.83" 8" Cable w/EXII-7710UC				

MICROTOUCH™ EX II TOUCH CONTROLLERS

MicroTouch™ EX II Controllers bring flexibility and feature-rich functionality to capacitive and resistive touch screen applications. With expanded regulatory approvals, improved power modes, and enhanced ESD and EMI protection, this controller series is a robust solution for popular touch applications

- Standard-setting ESD and EMI protection
- · Wide operating temperature

For quantities of 100 and up, call for quote.

MOUSER 3M Touch	F:	Dimensions	Power	Price Each			
STOCK NO.	STOCK NO. Systems Part No.		Fig. (mm)	Requirements	1	10	50
517-EXII-7760UC	EXII-7760UC	D	33.0 x 65.0 x 11.4	5Vdc ± 5% 105mA			
517-EXII-7719UC	EXII-7719UC	D	33.0 x 65.0 x 11.4	5Vdc ± 5% 105mA			
517-EXII-7720SC	EXII-7720SC	D	33.0 x 65.0 x 11.4	5-12Vdc ± 5% 85mA			

MICROTOUCH™ SC SERIES TOUCH CONTROLLERS

MicroTouch™ SC Controllers support 4-. 5-, and 8-wire resistive touch screens.

The high performance feature set with state-of-the-art components provides USB, HID and WHQL compliance.

Features:

- Fast and accurate touch response.
 Supports 4-, 5-, and 8-wire resistive touch screens.

For quantities of 100 and up, call for	auote

					 	4
517-SC401U	SC401U	Е	67.8 x 33.0 x 11.4	5Vdc ±10% 15mA		
517-SC402S	SC402S	E	69.1 x 39.9 x 11.4	12Vdc ±5% 19mA		
517-SC501U	SC501U	E	72.4 x 33.0 x 11.4	5Vdc ±10% 15mA		
517-SC502S	SC502S	E	70.4 x 39.9 x 11.4	12Vdc ±5% 19mA		
517-SC801U	SC801U	E	69.9 x 33.0 x 11.4	dc ±10% 15mA		
517-SC802S	SC802S	E	71.6 x 39.9 x 11.4	12Vdc ±5% 19mA		
517-SCX-ASIC	SCX-ASIC	Е		Based on design		

MICROTOUCH™ COMMUNICATION CABLES

Controller-to-CPU communication cables

For quantities of	100	and up	, call	for	quote.

MOUSER	SER Systems Fig. Description		ı	Price Each	1	
STOCK NO.	Part No.	Fig.	Description		10	50
517-7310101	7310101		CBL RS232, 2mm, 96"			
517-7312256	7312256		CBL USB Type A, 2mm, 96"			
517-7315050	7315050		CBL USB Type A, 2mm, 23"			
517-7319420	7319420		CBL USB Type A, WHQL for SCxxx, 2mm, 96"			
517-7319630	7319630		CBL RS232 Plug/Play for SCxxx, 96"			

3M VHB FOAM TAPE

3M VHB double-coated acrylic foam tapes utilize high performance adhesives which have excellent long-term holding power and are a preferred method for mounting touch sensors to LCD displays.

For quanti	ties of	100 and	up,	call for	quote.

- 3	illes of 100	and up, car	i ioi quote.			
MOUSER STOCK NO. 3M Touch Systems Part No.	F: «	Thickness	Price Each			
		Fig.	ITIICKITESS	1	10	50
517-24736	24736		50 x 0.062			











