

TEXAS INSTRUMENTS Analog ICs



Products may be RoHS compliant.
Check mouser.com for RoHS status.

TEXAS INSTRUMENTS PCI-EXPRESS

PCIe Endpoints

For quantities 500 and up, call for quote.

MOUSER STOCK NO.	TI Part No.	Package	1394a	Speed (Max) (Mbps)	FIFO (mb)	Supply Voltage	Price Each			
							1	25	100	250
595-XIO2200AGGW	XIO2200AGGW	BGA MICROSTAR-176	Yes	400	9	1.5, 3.3				
595-XIO2200AZHH	XIO2200AZHH	BGA MICROSTAR-175	Yes	400	9	1.5, 3.3				

PCIe PHYs

For quantities 500 and up, call for quote.

MOUSER STOCK NO.	TI Part No.	Package	Supply Voltage (Vcc) (nom)	PCIe	Parallel Bus Width	Speed (Max) (Gbps)	Price Each			
							1	25	100	250
595-XIO1100GGB	XIO1100GGB	BGA-100	1.5, 1.8, 3.3	X1	16, 8	2.5				
595-XIO1100ZGB	XIO1100ZGB	BGA-100	1.5, 1.8, 3.3	X1	16, 8	2.5				

TEXAS INSTRUMENTS RS-232

For quantities 500 and up, call for quote.

MOUSER STOCK NO.	TI Part No.	Package	Data Rate (kbps)	Driver Per Package	Receivers Per Package	ESD HBM (kV)	Supply Voltage	ICC (Max) (mA)	Price Each			
									1	25	100	250
595-SN75155D	SN75155D	SOIC-8	120	1	1	2	-12	14				
595-SN75155P	SN75155P	PDIP-8	120	1	1	2	-12	14				
595-MAX202CDR	MAX202CDR	SOIC-16	120	2	2	15	5	15				
595-MAX202CDWR	MAX202CDWR	SOIC-16	120	2	2	15	5	15				
595-MAX202ID	MAX202ID	SOIC-16	120	2	2	15	5	15				
595-MAX202IDWR	MAX202IDWR	SOIC-16	120	2	2	15	5	15				
595-MAX202IPW	MAX202IPW	TSSOP-16	120	2	2	15	5	15				
595-MAX222IDWR	MAX222IDWR	SOIC-18	120	2	2	15	5	10				
595-MAX232D	MAX232D	SOIC-16	120	2	2	2	5	10				
595-MAX232DW	MAX232DW	SOIC-16	120	2	2	2	5	10				
595-MAX232ID	MAX232ID	SOIC-16	120	2	2	2	5	10				
595-MAX232IDW	MAX232IDW	SOIC-16	120	2	2	2	5	10				
595-MAX232IN	MAX232IN	PDIP-16	120	2	2	2	5	10				
595-MAX232N	MAX232N	PDIP-16	120	2	2	2	5	10				
595-MAX232NSR	MAX232NSR	SO-16	120	2	2	2	5	10				
595-MAX232ECN	MAX232ECN	PDIP-16	120	2	2	±15	5	10				
595-SN75150P	SN75150P	PDIP-8	120	2	-	2	-12	22				
595-SN75C1406D	SN75C1406D	SOIC-16	120	3	3	2	±12, 5	0.45				
595-SN75C1406DW	SN75C1406DW	SOIC-16	120	3	3	2	±12, 5	0.45				
595-SN75C1406N	SN75C1406N	PDIP-16	120	3	3	2	±12, 5	0.45				
595-TL145406DW	TL145406DW	SOIC-16	120	3	3	2	±12, 5	20				
595-TL145406N	TL145406N	PDIP-16	120	3	3	2	±12, 5	20				
595-GD75232DBR	GD75232DBR	SSOP-20	120	3	5	-	±9, 5	30				
595-GD75232DW	GD75232DW	SOIC-20	120	3	5	-	±9, 5	30				
595-GD75232PWR	GD75232PWR	TSSOP-20	120	3	5	-	±9, 5	30				
595-SN75185DB	SN75185DB	SSOP-20	120	3	5	10	±12, 5	30				
595-SN75185DW	SN75185DW	SOIC-20	120	3	5	10	±12, 5	30				
595-SN75185N	SN75185N	PDIP-20	120	3	5	10	±12, 5	30				
595-SN75C185DW	SN75C185DW	SOIC-20	120	3	5	2	±12, 5	0.75				
595-SN75C185N	SN75C185N	PDIP-20	120	3	5	2	±12, 5	0.75				
595-SN75LBC187DBR	SN75LBC187DBR	SSOP-28	120	3	5	-	5	30				
595-MAX208CDBR	MAX208CDBR	SSOP-24	120	4	4	15	5	20				
595-MAX208CDWR	MAX208CDWR	SOIC-24	120	4	4	15	5	20				
595-MAX211CDBR	MAX211CDBR	SSOP-28	120	4	5	15	5	20				
595-MAX211CDW	MAX211CDW	SOIC-28	120	4	5	15	5	20				
595-MAX211IDBR	MAX211IDBR	SSOP-28	120	4	5	15	5	20				
595-SN75188D	SN75188D	SOIC-14	120	4	-	2	-9	25				
595-SN75188N	SN75188N	PDIP-14	120	4	-	2	-9	25				
595-SN75C188D	SN75C188D	SOIC-14	120	4	-	2	-12	0.16				
595-SN75C188N	SN75C188N	PDIP-14	120	4	-	2	-12	0.16				
595-MAX207CDBR	MAX207CDBR	SSOP-24	120	5	3	15	5	20				
595-SN75196DW	SN75196DW	SOIC-20	120	5	3	10	±12, 5	20				
595-SN75LV4737ADBR	SN75LV4737ADBR	SSOP-28	128	3	5	4	3 or 5	20.7				
595-MAX3221CDB	MAX3221CDB	SSOP-16	250	1	1	15	3.3, 5	1				
595-MAX3221CPW	MAX3221CPW	TSSOP-16	250	1	1	15	3.3, 5	1				
595-MAX3221IDBR	MAX3221IDBR	SSOP-16	250	1	1	15	3.3, 5	1				
595-MAX3221IPW	MAX3221IPW	TSSOP-16	250	1	1	15	3.3, 5	1				
595-MAX3223CDBR	MAX3223CDBR	SSOP-20	250	2	2	15	3.3, 5	1				
595-MAX3223CDWR	MAX3223CDWR	SOIC-20	250	2	2	15	3.3, 5	1				
595-MAX3223CPWR	MAX3223CPWR	TSSOP-20	250	2	2	15	3.3, 5	1				
595-MAX3223IDB	MAX3223IDB	SSOP-20	250	2	2	15	3.3, 5	1				
595-MAX3223IDWR	MAX3223IDWR	SOIC-20	250	2	2	15	3.3, 5	1				
595-MAX3223IPWR	MAX3223IPWR	TSSOP-20	250	2	2	15	3.3, 5	1				
595-MAX3243CDB	MAX3243CDB	SSOP-28	250	3	5	15	3.3, 5	1				

