


AX103713 Faceplates and Panels - FiberExpress Ultra Cassette



For more Information
please call

1-800-Belden1

Description:

FiberExpress Ultra Pre-terminated Cassette, 12 fibers, LC duplex-MPO multimode, OM3

Usage (Overall)

| | |
|-------------------------------|---|
| Suitable Applications: | FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room, Data Centers |
| Related Parts: | FiberExpress Ultra Patch panels, Pre-terminated MPO cable assemblies |

Physical Characteristics (Connectivity)

Capacity

Max. Capacity: 12 Fibers, 6 LC Duplex Bezels

Access

Front Connection: 1 inch Pullout

Dimensions

Dimensions:

| Height (in.) | Width (in.) | Length (in.) |
|--------------|-------------|--------------|
| 1.500 | 4.500 | 6.600 |

Materials

Materials:

| Description | Material |
|-------------|----------|
| Panel | Steel |

Color

Color: Aqua

Weight

Weight: 1.130 lbs.

Packaging

Packaging: Individually packaged in a Thermoformed packaging

Mechanical Characteristics (Connectivity)

Storage Temperature Range: -40°C To +80°C

Applicable Specifications and Agency Compliance (Overall)

Suitability

Suitability - Indoor: Yes

Transmission Characteristics (Connectivity)

Transmission Specifications:

| Description | Multimode | Singlemode |
|--------------------------------------|-------------|-------------|
| ST-type and SC-Duplex Insertion Loss | 1.50dB max | 1.25dB max |
| ST-type and SC-Duplex Reflectance | <-20dB | <-55dB |
| LC & Secure/Keyed LC Insertion Loss | 1.15 dB max | 1.15 dB max |
| LC & Secure/Keyed LC Reflectance | <-20 dB | <-50dB |
| MT-RJ Insertion Loss | 1.40 dB max | 1.40 dB max |
| MT-RJ Reflectance | <-20 dB | <-45 dB |

Notes (Overall)

Notes: For additional product family information, please refer to NPB285 (FiberExpress Ultra Cassettes)

Product Family

AX103713 Faceplates and Panels - FiberExpress Ultra Cassette

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|--------|-------|-------------|-------|-------|-----------|
|--------|-------|-------------|-------|-------|-----------|

Revision Number: 0 Revision Date: 11-22-2011

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.