


LITTELFUSE SIDACTor® Devices



Littelfuse® SIDACTOR® DEVICES

This product is RoHS compliant.



RoHS Compliant

DO-214AA SIDACTor solid state protection devices protect telecommunications equipment such as; modems, line cards, and CPE (telephones, answering machines, and fax machines).

For quantities of 50 and up, call for quote.

| MOUSER STOCK NO. | Littelfuse Part No. | Package | Volts | | | Idrm Uamps | Is mAmps | It Amps | Ih mAmps | Price Each | | | Price Per Reel | |
|------------------|---------------------|----------|-------|-----|----|------------|----------|---------|----------|------------|----|----|----------------|------|
| | | | Vdrm | Vs | Vt | | | | | 1 | 10 | 50 | Quantity | Each |
| 576-P0080SALRP | P0080SALRP | DO-214AA | 6 | 25 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P0080SBLRP | P0080SBLRP | DO-214AA | 6 | 25 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P0080SCLRP | P0080SCLRP | DO-214AA | 6 | 25 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P0220SALRP | P0220SALRP | DO-214AA | 15 | 32 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P0300SALRP | P0300SALRP | DO-214AA | 25 | 40 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P0300SBLRP | P0300SBLRP | DO-214AA | 25 | 40 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P0300SCLRP | P0300SCLRP | DO-214AA | 25 | 40 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P0640SALRP | P0640SALRP | DO-214AA | 58 | 77 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P0640SBLRP | P0640SBLRP | DO-214AA | 58 | 77 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P0640SCLRP | P0640SCLRP | DO-214AA | 58 | 77 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P0720SALRP | P0720SALRP | DO-214AA | 65 | 88 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P0720SBLRP | P0720SBLRP | DO-214AA | 65 | 88 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P0720SCLRP | P0720SCLRP | DO-214AA | 65 | 88 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P0900SALRP | P0900SALRP | DO-214AA | 75 | 98 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P0900SBLRP | P0900SBLRP | DO-214AA | 75 | 98 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P0900SCLRP | P0900SCLRP | DO-214AA | 75 | 98 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P1100SALRP | P1100SALRP | DO-214AA | 90 | 130 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P1100SBLRP | P1100SBLRP | DO-214AA | 90 | 130 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P1100SCLRP | P1100SCLRP | DO-214AA | 90 | 130 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P1300SALRP | P1300SALRP | DO-214AA | 120 | 160 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P1300SBLRP | P1300SBLRP | DO-214AA | 120 | 160 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P1300SCLRP | P1300SCLRP | DO-214AA | 120 | 160 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P1500SALRP | P1500SALRP | DO-214AA | 140 | 180 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P1500SCLRP | P1500SCLRP | DO-214AA | 140 | 180 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P1800SALRP | P1800SALRP | DO-214AA | 170 | 220 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P1800SBLRP | P1800SBLRP | DO-214AA | 170 | 220 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P1800SCLRP | P1800SCLRP | DO-214AA | 170 | 220 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P2300SALRP | P2300SALRP | DO-214AA | 190 | 260 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P2300SBLRP | P2300SBLRP | DO-214AA | 190 | 260 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P2300SCLRP | P2300SCLRP | DO-214AA | 190 | 260 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P2600SALRP | P2600SALRP | DO-214AA | 220 | 300 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P2600SBLRP | P2600SBLRP | DO-214AA | 220 | 300 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P2600SCLRP | P2600SCLRP | DO-214AA | 220 | 300 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P3100SALRP | P3100SALRP | DO-214AA | 275 | 350 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P3100SBLRP | P3100SBLRP | DO-214AA | 275 | 350 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P3100SCLRP | P3100SCLRP | DO-214AA | 275 | 350 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P3500SALRP | P3500SALRP | DO-214AA | 320 | 400 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P3500SBLRP | P3500SBLRP | DO-214AA | 320 | 400 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P3500SCLRP | P3500SCLRP | DO-214AA | 320 | 400 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |

Littelfuse® MICROCAPACITANCE (MC) SC SIDACTOR DEVICES



RoHS Compliant

These DO-214AA SCMC SIDACTor devices are intended for applications sensitive to load values. Typically, high speed connections, such as xDSL and T1/E1, require a lower capacitance. CO values for the MicroCapacitance device are 40 percent lower than a standard SC part.

For quantities of 50 and up, call for quote.

| MOUSER STOCK NO. | Littelfuse Part No. | Package | Volts | | | Idrm Uamps | Is mAmps | It Amps | Ih mAmps | Price Each | | | Price Per Reel | |
|------------------|---------------------|----------|-------|-----|----|------------|----------|---------|----------|------------|----|----|----------------|------|
| | | | Vdrm | Vs | Vt | | | | | 1 | 10 | 50 | Quantity | Each |
| 576-P0080SCMCLRP | P0080SCMCLRP | DO-214AA | 6 | 25 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P0300SCMCLRP | P0300SCMCLRP | DO-214AA | 25 | 40 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P0640SCMCLRP | P0640SCMCLRP | DO-214AA | 58 | 77 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P0900SCMCLRP | P0900SCMCLRP | DO-214AA | 75 | 98 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P1300SCMCLRP | P1300SCMCLRP | DO-214AA | 120 | 160 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P1800SCMCLRP | P1800SCMCLRP | DO-214AA | 170 | 220 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P2600SCMCLRP | P2600SCMCLRP | DO-214AA | 220 | 300 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |
| 576-P3100SCMCLRP | P3100SCMCLRP | DO-214AA | 275 | 350 | 4 | 5 | 800 | 2.2 | 150 | | | | 2500 | |

Littelfuse® HIGH SURGE CURRENT (D-RATED) SIDACTOR DEVICES



RoHS Compliant

DO-214AA SIDACTor solid state protection devices with a D surge rating protect telecommunications equipment located in hostile environments. Surge ratings are twice that of a device with a C surge rating.

For quantities of 50 and up, call for quote.

| MOUSER STOCK NO. | Littelfuse Part No. | Package | Volts | | | Idrm Uamps | Is mAmps | It Amps | Ih mAmps | Price Each | | | Price Per Reel | |
|------------------|---------------------|----------|-------|-----|----|------------|----------|---------|----------|------------|----|----|----------------|------|
| | | | Vdrm | Vs | Vt | | | | | 1 | 10 | 50 | Quantity | Each |
| 576-P0080SDLRP | P0080SDLRP | DO-214AA | 6 | 25 | 4 | 5 | 800 | 2 | 50 | | | | 2500 | |
| 576-P0640SDLRP | P0640SDLRP | DO-214AA | 58 | 77 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P0720SDLRP | P0720SDLRP | DO-214AA | 65 | 88 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P0900SDLRP | P0900SDLRP | DO-214AA | 75 | 98 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P1500SDLRP | P1500SDLRP | DO-214AA | 140 | 180 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P1800SDLRP | P1800SDLRP | DO-214AA | 170 | 220 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P2300SDLRP | P2300SDLRP | DO-214AA | 190 | 260 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P2600SDLRP | P2600SDLRP | DO-214AA | 220 | 300 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P3100SDLRP | P3100SDLRP | DO-214AA | 275 | 350 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |
| 576-P3500SDLRP | P3500SDLRP | DO-214AA | 320 | 400 | 4 | 5 | 800 | 2.2 | 50 | | | | 2500 | |