

SPECIFICATION

- Part No. : **AP.10G.01**
- Product Name : 10mm SMT 14dB Active GPS Patch Antenna
With Front End Saw Filter
- Features : Unique SMT GPS active patch
Wide Input Voltage 1.5V to 3.3V
Ultra low power consumption
RoHS compliant
- Photo :




1.0 Introduction

The AP.10G.01 one stage 14dB active GPS patch antenna is the smallest SMT GPS high performance embedded antenna currently available in the world. Using extremely sensitive high dielectric constant powder formulation and tight process control the 10mm x 10mm x 4mm patch antenna is accurately tuned to have its frequency band right at 1575.42MHz for GPS systems.

A patented SMT structure gives high reliability in integration. With an ultra low power consumption one stage LNA with Saw Filter , this small active patch has the performance of an ordinary active patch, but at only a quarter of the size. This product is suited to small form factor mobile devices such as GPS Smartphones, Personal Location, Medical devices, Telematic devices and Automotive navigation and tracking. Custom gain, connector and cable versions are available.

The AP.10G consists of 2 functional blocks – the LNA and also the patch antenna.



2.0 Specification

2.1 Patch Antenna

Parameter	Specification
Frequency	1575.42 ± 1.023MHz
Gain	Typ -10dBic @ Zenith
Impedance	50Ω
Polarization	RHCP
Axial Ratio	Max 4.0dB @ Zenith
Dimension	10mm x 10mm x 4mm (add 7.3mm depth for vertical PCB)


2.2 LNA

Parameter	Specification		
Frequency	1575.42 ± 1.023MHz		
Outer Band Attenuation	F0=1575.42MHz F0±30MHz 9dB min. F0±50MHz 14dB min. F0±100MHz 18dB min.		
Output Impedance	50Ω		
Output VSWR	2.0 Max		
Pout at 1dB Gain Compression point	Typ. 1dBm		
LNA Gain, Power Consumption and Noise Figure			
Voltage	LNA Gain (Typ)	Power Consumption(mA) Typ	Noise Figure Typ
Min. 1.5V	18dB	3.5mA	2.6dB
Typ. 1.8V	18dB	3.5mA	2.6dB
Max. 3.3V	18dB	3.5mA	2.6dB


2.3 Connection

Connection	SMT via solder pads
------------	---------------------

3.0 LNA Gain and Out Band Rejection @3.0V



4.0 LNA Noise Figure @3.0V




5.0 Total Specification

(through Antenna, LNA)


Parameter	Specification
Frequency	1575.42 ± 1.023MHz
Gain	8 ± 4dBic @ 90°
Output Impedance	50 Ω
Polarization	RHCP
Output VSWR	Max 2.0
Operation Temperature	-20°C to + 85°C
Storage Temperature	-30°C to + 85°C
Relative Humidity	40% to 95%
Input Voltage	Min. 1.5V, Typ. 1.8V, Max. 3.3V

6.0 Radiation Patterns

6.1 XZ Plane




6.2 YZ Plane




Pattern	Model No.	Test Mode	Freq(MHz)	Max Gain(dBi)	Min Gain(dBi)	Avg. Gain(dBi)	Source Polar.	Date
1	1620	YZ	1620.00	-9.73 / 324.00	-19.18 / 222.00	-12.80	RHCP	2010/4/29

6.3 XY Plane








Pattern	Model No.	Test Mode	Freq(MHz)	Max Gain(dBi)	Min Gain(dBi)	Avg. Gain(dBi)	Source Polar.	Date
1	1620	XZ	1620.00	-9.20 / 42.00	-11.99 / 147.00	-10.24	RHCP	2010/4/29
2	1620	YZ	1620.00	-9.73 / 324.00	-19.18 / 222.00	-12.80	RHCP	2010/4/29

7.0 Technical Drawing



	Name	Material	Finish	QTY
1	Patch (10mmx10mmx4.2mm)	Ceramic	Clear	1
2	Shielding Case	Tin (SPTE)	Tin Plated	1
3	PCB	FR4 0.6t	Green	1

Note:

- 1. Soldered Area 
- 2. Solder Mask Area (Green) 
- 3. Clearance Area 
- 4. Shielding Case Area 
- 5. Area to be solder (Pad) 

8.0 Packaging

Packaged on Tape and Reel – 250 pieces per reel
Each Reel is packaged – Inner Carton
Outer Carton contains 5 Reels – 1250 pieces per Carton

